

Class-D Module. Com Single Channel Series		Class-D Module. Com Single Channel Series	
Model	L1.1C1	Model	L1.2C1
Size	90mm X 253mm X 75mm (WxLxH)	Size	90mm X 300mm X 75mm (WxLxH)
describtion	High power single channel full-range (variable low cut 33-200Hz) or subwoofer (variable high cut 33-200Hz). Please specifiy when ordering	describtion	High power single channel full-range (variable low cut 33-200Hz) or subwoofer (variable high cut 33-200Hz). Please specifiy when ordering
Output power	250W@8OHM 500W@4Ohm	Output power	500W@8OHM 1000W@4Ohm
Total Frequency Response	20Hz~20KHz (d1dB)	Frequency Response	20Hz~20KHz (d1dB)
Distortion rate	THD<0.1% (full loading)	Distortion rate	THD<0.1% (full loading)
Power Frequency load	125KHz(PWM)*1	Power Frequency load	125KHz(PWM)*1
power response Frequency	>5KHz	power response Frequency	>5KHz
amplifier Frequency load	392KHz (d5%)	amplifier Frequency load	392KHz (d5%)
input impendance	balance input 40KOHM/unbalance input 20KOHM	input impendance	balance input 40KOHM/unbalance input 20KOHM
input/output	Single channel balance input, LINK output ; Optional full-range or subwoofer, HPF/LPF between 25Hz~200Hz。	input/output	Single channel balance input, LINK output ; Optional full-range or subwoofer, HPF/LPF between 25Hz~200Hz。
Pictures		Pictures	